

xls-hashimoto 式計算方法とJAEA-Technology 2011-026との比較

除染半径 (m)	<i>xls-hashimoto</i> 式算出方法				JAEA-Technology 2011-026			<i>xls</i> / JAEA		
	単位円線量率 ($\mu\text{Sv/h}$)	算出線量率 ($\mu\text{Sv/h}$)	線量率低減比	低減効果 (%)	線量率 ($\mu\text{Sv/h}$)	線量率低減比	低減効果 (%)	線量率	低減比	低減効果
0	1.18E-05	3.08E+00	1.00E+00	0	3.08E+00	1.00E+00	0	1.00	1.00	
10	6.76E-04	1.41E+00	4.59E-01	54	1.60E+00	5.19E-01	48	0.88	0.88	1.13
20	3.10E-04	9.61E-01	3.12E-01	69	1.09E+00	3.53E-01	65	0.88	0.88	1.06
50	9.42E-05	4.54E-01	1.47E-01	85	6.82E-01	2.22E-01	78	0.67	0.66	1.10
80	4.46E-05	2.58E-01	8.39E-02	92	4.54E-01	1.47E-01	85	0.57	0.57	1.07
100	2.96E-05	1.85E-01	6.02E-02	94	3.41E-01	1.11E-01	89	0.54	0.54	1.06
150	1.24E-05	8.78E-02	2.85E-02	97	2.01E-01	6.54E-02	93	0.44	0.44	1.04
200	5.86E-06	4.44E-02	1.44E-02	99	1.18E-01	3.83E-02	96	0.38	0.38	1.02
400	4.59E-07	3.59E-03	1.17E-03	100	1.78E-02	5.80E-03	99	0.20	0.20	1.00