

*xls-hashimoto* 式計算方法とJAEA-Technology 2011-026との比較

除染半径 (m)	<i>xls-hashimoto</i> 式算出方法				JAEA-Technology 2011-026			<i>xls</i> / JAEA		
	単位円線量率 ( $\mu\text{Sv/h}$ )	算出線量率 ( $\mu\text{Sv/h}$ )	線量率低減比	低減効果 (%)	線量率 ( $\mu\text{Sv/h}$ )	線量率低減比	低減効果 (%)	線量率	低減比	低減効果
0	1.73E-06	2.68E+00	1.00E+00	0	3.08E+00	1.00E+00	0	0.87	1.00	
10	9.87E-05	1.23E+00	4.59E-01	54	1.60E+00	5.19E-01	48	0.77	0.88	1.13
20	4.53E-05	8.36E-01	3.12E-01	69	1.09E+00	3.53E-01	65	0.77	0.88	1.06
50	1.38E-05	3.95E-01	1.47E-01	85	6.82E-01	2.22E-01	78	0.58	0.66	1.10
80	6.51E-06	2.25E-01	8.39E-02	92	4.54E-01	1.47E-01	85	0.50	0.57	1.07
100	4.33E-06	1.61E-01	6.02E-02	94	3.41E-01	1.11E-01	89	0.47	0.54	1.06
150	1.82E-06	7.64E-02	2.85E-02	97	2.01E-01	6.54E-02	93	0.38	0.44	1.04
200	8.57E-07	3.87E-02	1.44E-02	99	1.18E-01	3.83E-02	96	0.33	0.38	1.02
400	6.70E-08	3.12E-03	1.17E-03	100	1.78E-02	5.80E-03	99	0.18	0.20	1.00